


TECHNICAL DATA

GLASS CLOTH TAPE Product Code: 1G155

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093
E-mail : sales@pleo.com * Web Site : <http://www.pleo.com>



UL FILE #E126174

Description : 1G155 is a Glass Cloth Tape with acrylic adhesive. It is designed to offer efficiencies in application and versatility in selection.

Application : Coil wrap, crossover insulation, coil banding.

Features/Benefits : Resistance to flagging and varnish solvents. Razor slitting is used to provide fray-free edges.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	COLOR	-	white
	TOTAL THICKNESS	mm	0.175
	BACKING THICKNESS	mm	0.125
	TENSILE STRENGTH	kg/25mm	72.273
	ELONGATION AT BREAK	%	8
	ADHESION TO STEEL	kg/25mm	0.852
	BREAKDOWN VOLTAGE	kV	1.5
	TEMPERATURE CLASS	°C	155

Availability : Standard 55M roll, 3" core, width 600mm

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

