


# TECHNICAL DATA

## COMPOSITE TAPE Product Code: 1H860

### P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.  
Telephone : (852) 2604-8222 \* Facsimile : (852) 2693-2093  
E-mail : sales@pleo.com \* Web Site : <http://www.pleo.com>



 UL FILE #E126174

Description : 1H860 is composed of 0.038mm polyester film reinforced/laminated with polyester non-woven coated with acrylic adhesive. Excellent solvent resistant and quick grab property, tough and conformable over irregular surfaces, outstanding adhesion. CTI grade PLC=0 as Group 1 materials.

Application : Ideal for insulating, banding, anchoring, holding in motors and transformers.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	BACKING THICKNESS	mm	0.038
	TOTAL THICKNESS	mm	0.15 ± 0.01
	TENSILE STRENGTH	kg/25mm	10
	ELONGATION	%	70
	ADHESION TO STEEL	kg/25mm	0.6
	DIELECTRIC BREAKDOWN	kV	5
	TEMPERATURE CLASS	°C	130

Test Method : In accordance with ASTM D-1000 method

Shelf Life : 6 months when storage at 73F and 65% relative humidity

Availability : Standard 60M roll, 3" core, width 1060mm

### Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or \*he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

