

TECHNICAL DATA

NOMEX® ARAMID PAPER TAPE

Product Code: 1N020

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093
E-mail : sales@pleo.com * Web Site : <http://www.pleo.com>



UL FILE #E126174

Description : 1N020 is NOMEX® paper 2mil (0.05mm) thick coated with Acrylic based adhesive, excellent Solvent resistant.

Application : For use in construction of transformers and electric motors, coil wrapping, capacitors, insulation of electrical parts which are to be impregnated and baked. Excellent varnish absorbability. It is use in Electrical insulation system up to Class H.

Technical Details :	<u>PROPERTIES</u>	<u>UNITS</u>	<u>SPECIFICATION</u>
	COLOR	-	White
	TOTAL THICKNESS	mm	0.09 ± 0.01
	BACKING THICKNESS	mm	0.05
	TENSILE STRENGTH	kg/25mm	10
	ELONGATION	%	10
	ADHESION TO STEEL	kg/25mm	0.5
	DIELECTRIC BREAKDOWN	kV	2.5
	TEMPERATURE RATING	°C	155

*NOMEX is a registered trademark of DUPONT

Test Method : In accordance with ASTM method

Shelf Life : 2 months when storage at 23°C and 65% relative humidity

Availability : Standard 30M roll, 3" core, width 440 mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.



**HALOGEN
FREE**

